Regent 1200





105

Emmet



180

Longreach



300

Brokenhill



350

Cobar



380

Birdsville



545

Georgetown



550

Melrose



555

Charleville



560

Burke



700

Silverton



740

Winton



790

Stamford

Specifications and colourations are subject to manufacturing tolerances. As part of the Godfrey Hirst continuous improvement program, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

Regent 1200

Regent 1200 from Godfrey Hirst is a versatile vinyl plank flooring range designed to combine the **natural appeal of timber with the practicality of modern vinyl construction**. Featuring a carefully curated palette of warm, contemporary tones, it provides a stylish and welcoming foundation suited to a wide range of interior styles.

Available in two formats, Regent allows you to tailor the look and scale of your space. **Regent 1200 features a shorter plank format, providing a more compact and versatile layout option**, while Regent 1500 offers a longer, slightly thicker plank for enhanced flow and a more expansive appearance across larger areas. Both formats share the same colour palette, allowing for design consistency across different spaces.

The embossed surface texture and matte finish enhance the realism of each plank, while the clean square edge profile delivers a modern, streamlined aesthetic. Built for everyday living, Regent delivers waterproof performance and a durable PUR protective coating that helps resist scratches, stains and general wear. Its** resilient construction ensures long-term performance**, while the direct stick installation method provides a secure, professional finish suitable for both renovations and new builds.

Technical Data

Type:	Vinyl Plank Flooring
Total Product Thickness:	2.5mm
Units Per Box:	18 boards
m² per pallet:	215.05
Country of Origin:	South Korea
Surface:	Embossed
Coating System:	PUR

Dimensions:	1219mm x 178mm
Wear Layer:	0.5mm
m² per box:	3.91
Colours:	12
Finish:	Matte
Profile:	Square Edge
Installation Method:	Direct Stick

Performance

Dimensional Stability:	(ISO 23999) Length: 0.05%, Width: 0.05%, Curling: 0.00%
Abrasion Rating:	(EN 660-2) Group T
Light Fastness:	(EN ISO 105-B02) 6-7
Flammability:	(EN ISO 9239) CRF 8.1kW/m2
Slip Resistance:	(AS 4586) P3

Thermal Conductivity:	TBA
Impact Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Light Reflectance Values:	105 - 42.44 | 180 - 11.05 | 300 - 22.14 350 - 13.58 | 380 - 13.05 | 545 - 19.96 550 - 14.12 | 555 - 16.23 | 560 - 19.50 700 - 39.08 | 740 - 25.84 | 790 -13.49
Smoke Value:	Direct Stick: (EN ISO 9239) 135% minutes | With Underlay: (EN ISO 9239) 179% minutes
Warranty:	25 Year Vinyl Plank Limited Residential Warranty*

Sustainability

Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits

Regent 1200



0.5mm Wear Layer



Matte Finish




ISO 9001 Quality Management System



ISO 14001 Environment Management System



Embossed



Square Edge



25 Year Vinyl Plank Limited Residential Warranty*



Affordable



Colour Variation



ECS Level 1



Waterproof Surface



Waterproof Core



Waterproof

Regent 1200

All Godfrey Hirst vinyl Plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Vinyl Plank Flooring Installation Instructions.
*This product comes with a residential warranty for new product installed indoors in a residential home, if properly installed and maintained. This warranty is in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under this warranty. The amount recoverable under the warranty decreases after five years. For full information in respect to the scope and limitations of this warranty, please refer to the to the full terms and conditions available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com.
Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.