Texmark





180

Harvey Tan



300

Patagonia Light



325

Duke Natural



505

Denia Light



510

Lumber Neutral



530

Bari Sand



535

Copenhagen Mid



540

Patagonia Honey



545

Blackbutt Summer



546

Blackbutt Classic



555

Spotted Gum Coastal



556

Spotted Gum Almond



560

Copenhagen Warm




705

Duke Grey



725

Padua Granite



730

Denia Ash

Specifications and colourations are subject to manufacturing tolerances. As part of the Godfrey Hirst continuous improvement program, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.


godfreyhirst.com

Texmark



780

Bari Stone



795

Denia Dusk

Texmark

Bring understated style and everyday practicality into your space with Texmark vinyl sheet flooring from Godfrey Hirst. Designed to capture a relaxed, natural aesthetic, its subtle surface detailing and contemporary designs create a versatile foundation that complements a wide range of interior styles, from modern to timeless.

Featuring a natural-inspired appearance with understated surface detail, Texmark offers a considered balance of style and functionality. Its versatile design makes it easy to coordinate with different furnishings, finishes and colour palettes, creating a welcoming foundation for a variety of interiors.

Designed for everyday living, Texmark combines durable performance with easy-care convenience and comfortable underfoot appeal. Suitable for both busy homes and commercial environments, its practical construction makes it a versatile flooring solution for spaces that require lasting functionality without compromising on style. **Texmark brings together relaxed design, everyday durability and easy maintenance for practical, stylish interiors.**

Technical Data

Type:	Vinyl Sheet Flooring
Wear Layer:	0.4mm
Finish:	Matte

Total Product Thickness:	2.8mm
Colours:	18
Installation Method:	Direct Stick

Performance

Impact Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Smoke Value:	Direct Stick: (EN ISO 9239) 124% minutes

Flammability:	(EN ISO 9239) CRF 5.7W/m2
Slip Resistance:	P3

Sustainability

Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits



Heavy Traffic



Affordable



European Made