Legacy 1200





170

Rustic Bronze



320

Amber Glow



510

Harbour Oak



520

Sunset Birch



525

Alpine Blackbutt



530

Coastal Driftwood



545

Eastern Blackbutt



550

Evening Haze



560

Mocha Java



700

Pebble Bay



730

Seaside Oak



790

Ebony Ash

Specifications and colourations are subject to manufacturing tolerances. As part of the Godfrey Hirst continuous improvement program, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

Legacy 1200

Bring depth, texture and contemporary style into your home with Legacy 1200 laminate flooring from Godfrey Hirst. **Designed to capture the authentic character of timber**, its embossed surface, matte finish and four-sided bevelled edges create a refined, natural-looking floor that complements both modern and timeless interiors.

Available in a carefully curated palette of contemporary timber décors, Legacy 1200 **delivers the warmth and visual appeal of natural wood with the practical benefits of laminate flooring**. Its water-resistant construction provides added confidence for busy households, while the durable AC4 abrasion rating helps maintain its beautiful appearance in the demands of everyday family living.

Designed for reliable performance, Legacy 1200 features a high-density fibreboard core for lasting stability and a Uniclic® locking system for efficient installation. With a P3 slip resistance rating, Green Building Council of Australia compliant VOC emission standards and a 20 Year Laminate Limited Residential Warranty*, Legacy 1200 offers **a dependable flooring solution that combines everyday durability with timeless style**.

Technical Data

Type:	Laminate Flooring
Total Product Thickness:	8mm
m² per box:	2.16
Colours:	12
Surface:	Embossed
Backing Layer:	Balancing Layer
Installation Method:	Uniclic®

Dimensions:	1216mm x 197mm
Units Per Box:	9 boards
m² per pallet:	140.14
Finish:	Matte
Substrate Layer:	860kg/m3 High Density Fibreboard
Profile:	4 Sided Bevel

Performance

Abrasion Rating:	(EN 13329) AC4
Flammability:	(EN ISO 9239) CRF 11kW/m2
Slip Resistance:	(AS/NZ 4586-2013) P3

Impact Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Smoke Value:	(EN ISO 9239) 4% minutes
Warranty:	20 Year Laminate Limited Residential Warranty*

Sustainability

Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits



ISO 9001 Quality Management System



ISO 14001 Environment Management System




Matte Finish


Uniclic® Watertight Locking System



Mid Range


4 Sided Bevel

Legacy 1200



Embossed



20 Year Laminate Limited Residential Warranty*



Celebrating Australian Species



Water Resistant



72 Hour Water Resistance

Legacy 1200

All Godfrey Hirst Laminate products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Laminate Flooring Installation Instructions.
*This product comes with a residential warranty for new product installed indoors in a residential home, if properly installed and maintained. This warranty is in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under this warranty. The amount recoverable under the warranty decreases after five years. For full information in respect to the scope and limitations of this warranty, please refer to the to the full terms and conditions available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com.
Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.